

1 . Product and company identification

| | |
|------------------------------------|---|
| Trade name | : Amazing Goop - Automotive, Craft, Household, Lawn & Garden, Marine, Plumbing, RV, Sport & Outdoor, Wood & Furniture |
| Supplier | : Eclectic Products Inc. 1075 Arrowsmith Eugene, OR 97402 541-484-9621 |
| Material uses | : Consumer products: Adhesive. |
| Manufacturer | : Eclectic Products Inc. 1075 Arrowsmith Eugene, OR 97402 541-484-9621 |
| Code | : 1000021 |
| Validation date | : 11/19/2009. |
| Print date | : 11/19/2009. |
| Responsible name | : Regulatory Compliance |
| <u>In case of emergency</u> | : CALL INFOTRAC 800-535-5053 001-352-323-3500 |

2 . Hazards identification

| | |
|--|---|
| Physical state | : Liquid. |
| Emergency overview | : WARNING ! FLAMMABLE LIQUID AND VAPOR. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY BE HARMFUL IF SWALLOWED. Flammable liquid. Harmful if swallowed. Irritating to eyes, respiratory system and skin. Keep away from heat, sparks and flame. Do not ingest. Avoid breathing vapor or mist. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling. |
| Routes of entry | : Dermal contact. Eye contact. Inhalation. |
| <u>Potential acute health effects</u> | |
| Inhalation | : Irritating to respiratory system. |
| Ingestion | : Harmful if swallowed. |
| Skin | : Irritating to skin. |
| Eyes | : Irritating to eyes. |
| <u>Potential chronic health effects</u> | |
| Chronic effects | : No known significant effects or critical hazards. |
| Carcinogenicity | : No known significant effects or critical hazards. |
| Mutagenicity | : No known significant effects or critical hazards. |
| Teratogenicity | : No known significant effects or critical hazards. |
| Developmental effects | : No known significant effects or critical hazards. |
| Fertility effects | : No known significant effects or critical hazards. |
| Target organs | : Contains material which may cause damage to the following organs: kidneys, liver, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea. |
| <u>Over-exposure signs/symptoms</u> | |
| Inhalation | : Adverse symptoms may include the following: respiratory tract irritation coughing |
| Ingestion | : No specific data. |

2 . Hazards identification

- Skin** : Adverse symptoms may include the following:
irritation
redness
- Eyes** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Medical conditions aggravated by over-exposure** : Pre-existing digestive disorders may be aggravated by over-exposure to this product.

See toxicological information (section 11)

3 . Composition/information on ingredients

| <u>Name</u> | <u>CAS number</u> | <u>%</u> |
|----------------|-------------------|----------|
| Toluene | 108-88-3 | 30-60 |
| Solvent Naptha | 64742-89-8 | 10-30 |

There are no ingredients or additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4 . First aid measures

- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Inhalation** : Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5 . Fire-fighting measures

- Flammability of the product** : Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Extinguishing media

- Suitable** : Use dry chemical, CO₂, water spray (fog) or foam.

5 . Fire-fighting measures

- Not suitable** : Do not use water jet.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Hazardous combustion products** : Decomposition products may include the following materials:
carbon oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8 . Exposure controls/personal protection

Product name

Toluene

Exposure limits

NIOSH REL (United States, 6/2008).

STEL: 560 mg/m³ 15 minute(s).

STEL: 150 ppm 15 minute(s).

TWA: 375 mg/m³ 10 hour(s).

TWA: 100 ppm 10 hour(s).

OSHA PEL Z2 (United States, 11/2006).

AMP: 500 ppm 10 minute(s).

CEIL: 300 ppm

TWA: 200 ppm 8 hour(s).

ACGIH TLV (United States, 1/2008).

TWA: 20 ppm 8 hour(s).

OSHA PEL 1989 (United States, 3/1989). Notes: See Table Z-2.

STEL: 560 mg/m³ 15 minute(s).

STEL: 150 ppm 15 minute(s).

TWA: 375 mg/m³ 8 hour(s).

TWA: 100 ppm 8 hour(s).

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal protection

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls


: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9 . Physical and chemical properties

Physical state

: Liquid.

Flash point

:  Open cup: 7.2222°C (45°F) []

Color

: Clear.

Odor

: Not available.

Boiling/condensation point

: 114.83°C (238.7°F)

Specific gravity

: 0.91 to 0.97

Vapor pressure

: 2.9 kPa (22 mm Hg)

Estimated Vapor Density

: 3.2 [Air = 1]

9 . Physical and chemical properties

| | |
|-------------------------|---------------------------|
| VOC % | : 54.999% |
| Evaporation rate | : >1 (Butyl acetate. = 1) |
| Solubility | : Not available. |

10 . Stability and reactivity

| | |
|---|--|
| Stability | : The product is stable. Under normal conditions of storage and use, hazardous polymerization will not occur. |
| Conditions to avoid | : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas. |
| Materials to avoid | : Reactive or incompatible with the following materials: oxidizing materials |
| Hazardous decomposition products | : Under normal conditions of storage and use, hazardous decomposition products should not be produced. |
| Hazardous polymerization | : Will not occur. |

11 . Toxicological information

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|--------------------------------|------------------|----------------|-------------|-----------------|
| Toluene | LD50 Dermal | Rabbit | 14100 uL/kg | - |
| | LD50 | Rat | 1332 mg/kg | - |
| | Intraperitoneal | | | |
| | LD50 Intravenous | Rat | 1960 mg/kg | - |
| | LD50 Oral | Rat | 636 mg/kg | - |
| | LD50 Unreported | Rat | 6900 mg/kg | - |
| | LDLo | Rat | 2.5 mL/kg | - |
| | Intraperitoneal | | | |
| | TDLo Oral | Rat | 400 mg/kg | - |
| | TDLo Oral | Rat | 800 mg/kg | - |
| | TDLo Oral | Rat | 800 mg/kg | - |
| | TDLo Oral | Rat | 1200 mg/kg | - |
| | TDLo | Rat | 900 mg/kg | - |
| | Intraperitoneal | | | |
| | TDLo | Rat | 750 mg/kg | - |
| | Intraperitoneal | | | |
| | TDLo | Rat | 750 mg/kg | - |
| | Intraperitoneal | | | |
| | TDLo | Rat | 1 gm/kg | - |
| | Intraperitoneal | | | |
| | TDLo | Rat | 600 mg/kg | - |
| | Intraperitoneal | | | |

Carcinogenicity

Conclusion/Summary

IDLH : Not available.

Synergistic products : Not available.

12 . Ecological information

Environmental effects : No known significant effects or critical hazards.

Aquatic ecotoxicity

| Product/ingredient name | Test | Result | Species | Exposure |
|--------------------------------|-------------|--|----------------------------------|-----------------|
| Toluene | - | Acute EC50 19600 ug/L Fresh water | Daphnia - Daphnia magna | 48 hours |
| | - | Acute EC50 6880 to 9830 ug/L Fresh water | Daphnia - Daphnia magna | 48 hours |
| | - | Acute EC50 6780 to 7810 ug/L Fresh water | Fish - Oncorhynchus mykiss | 96 hours |

12 . Ecological information

| | | | |
|---|--|-------------------------------|----------|
| - | Acute EC50 6000 ug/L Fresh water | Daphnia - Daphnia magna | 48 hours |
| - | Acute LC50 9360 ug/L Fresh water | Fish - Oncorhynchus kisutch | 96 hours |
| - | Acute LC50 8110 ug/L Fresh water | Fish - Oncorhynchus kisutch | 96 hours |
| - | Acute LC50 8090 to 8780 ug/L Marine water | Fish - Oncorhynchus gorboscha | 96 hours |
| - | Acute LC50 7630 to 8480 ug/L Marine water | Fish - Oncorhynchus gorboscha | 96 hours |
| - | Acute LC50 97700 to 174700 ug/L Fresh water | Daphnia - Daphnia magna | 48 hours |
| - | Acute LC50 6780 to 7810 ug/L Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| - | Acute LC50 6410 to 7180 ug/L Marine water | Fish - Oncorhynchus gorboscha | 96 hours |
| - | Acute LC50 86300 to 174700 ug/L Fresh water | Daphnia - Daphnia magna | 48 hours |
| - | Acute LC50 5800 ug/L Fresh water | Fish - Oncorhynchus mykiss | 96 hours |
| - | Acute LC50 5500 ug/L Fresh water | Fish - Oncorhynchus kisutch | 96 hours |
| - | Acute LC50 310000 to 420000 ug/L Fresh water | Daphnia - Daphnia magna | 48 hours |
| - | Acute LC50 7.3 ul/L Marine water | Fish - Morone saxatilis | 96 hours |

Conclusion/Summary : Not available.

Biodegradability

Conclusion/Summary : Not available.




13 . Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14 . Transport information

| Regulatory information | UN number | Proper shipping name | Classes | PG* | Label | Additional information |
|---------------------------|----------------|----------------------|---------|-----|---|---|
| DOT Classification | Not available. | Consumer commodity | ORM-D | - | | Limited quantity Yes. Remarks < . 3 gal Consumer commodity ORM-D |
| TDG Classification | 1133 | ADHESIVES | 3 | II |  | Explosive Limit and Limited Quantity Index 5 Passenger Carrying Road or Rail Index 5 |
| IMDG Class | 1133 | ADHESIVES | 3 | II |  | Emergency schedules (EmS) F-E,S-D Remarks Limited quantity |
| IATA-DGR Class | 8000 | Consumer commodity | 9 | - |  | - |

PG* : Packing group

15 . Regulatory information

U.S. Federal regulations : **United States inventory (TSCA 8b):** All components are listed or exempted.
SARA 311/312 - fire, Acute, Chronic

SARA 313

Form R - Reporting requirements

: **Product name**
Toluene

CAS number
108-88-3

Concentration
30-60

This product contains toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986, and subpart C-Supplier Notification Requirement of 40 CFR Part 372.

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

State regulations

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name
Toluene

Cancer
No.

Reproductive
Yes.

Canada

WHMIS (Canada)

: Class B-2: Flammable liquid
Class D-2A: Material causing other toxic effects (Very toxic).
Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists

: **CEPA Toxic substances:** None of the components are listed.

Canadian NPRI: The following components are listed: Toluene;Solvent naphtha light aliphatic

Canada inventory

: **Canada inventory:** All components are listed or exempted.

15 . Regulatory information

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

Mexico

Classification :



EU regulations

Hazard symbol or symbols :



Risk phrases

- : R11- Highly flammable.
R45- May cause cancer.
R63- Possible risk of harm to the unborn child.
R48/20- Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R38- Irritating to skin.
R67- Vapors may cause drowsiness and dizziness.

Safety phrases

- : S53- Avoid exposure - obtain special instructions before use.
S2- Keep out of the reach of children.
S36/37- Wear suitable protective clothing and gloves.
S46- If swallowed, seek medical advice immediately and show this container or label.

International regulations

International lists

- : Australia inventory (AICS): Not determined.
China inventory (IECSC): Not determined.
Korea inventory (KECI): Not determined.
Philippines inventory (PICCS): Not determined.
Japan inventory (ENCS): Not determined.
Europe inventory: Not determined.

16 . Other information

Hazardous Material
Information System (U.S.A.) :

| | | |
|------------------|---|---|
| Health | * | 2 |
| Flammability | | 3 |
| Physical hazards | | 0 |
| | | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection
Association (U.S.A.) :



16 . Other information

Date of printing : 11/19/2009.

Date of issue : 11/19/2009.

Date of previous issue : 11/19/2009.

Version : 1.03

 Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.