COVENTRY Handlesets Entry (Springdale)

Specifications

Latch Type	2-Way Latch & Universal Latch available
Door Prep	Cross bore 2-1/8" dia (54mm). Edge bore 1" dia (25mm)
Backset	Adjustable to 2-3/8" or 2-3/4"
Door Thickness	1-3/8" - 1-3/4" door standard
Cylinder	5-pin High Security - removable core
Faceplate	1" x 2-1/4" radius corner. (Square and drive-in also available on Universal)
Strike	Standard radius corner . Other options available.
Latch Bolt	(Full 1/2" throw Handleset), (Full 1" throw Deadbolt). Nickel plated.
Door Handing	Non-handed. Reversible for Left or Right hand doors.
Keyway	KW1


KD - keyed different


1-15/16"

Keyed Alike

Dimensions

2-5/8"





Warranty & Compliances

Warranty	Limited Lifetime Mechanical / 5 year Finish	Hartis Akto	
ANSI/BHMA	Meets ANSI Grade 3 specification	GRADE 3 UFETIM	A TAR
ADA	N/A		•
UL	N/A		

Order Codes

View Pack	
Satin Nickel (US15)	
Polished Brass (US3)	
Oil Rubbed Bronze (US10B)	

 2W
 Universal

 700682
 754499

 700559
 754481

 700567
 754507

 Type: Job: Order Code: Approvals:

Design House reserves the right to make changes in materials, specifications & models at any time. Design House also reserves the right to discontinue product without notice or obligation

