COVENTRY Handlesets Entry (Scroll)



Specifications

 Latch Type
 2-Way Latch & Universal Latch available

Door Prep Cross bore 2-1/8" dia (54mm). Edge bore 1" dia

(25mm

Backset Adjustable to 2-3/8" or 2-3/4" **Door Thickness** 1-3/8" - 1-3/4" door standard

Cylinder 5-pin High Security - removable core

Faceplate 1" x 2-1/4" radius corner. (square corner & 6W or

drive-in also available)

Strike Standard radius corner . Other options available.

Latch Bolt (Full 1/2" throw Handleset),


(Full 1" throw Deadbolt). Nickel plated.

Door Handing Non-handed. Reversible for Left or Right hand doors.

Keyway KW1

Keyed Alike KD - keyed different

Dimensions



Warranty & Compliances

Warranty Limited Lifetime Mechanical / 5 year Finish

ANSI/BHMA Meets ANSI Grade 3 specification

ADA N/A UL N/A







Order Codes

View Pack	2W	Universal		
Satin Nickel (US15)	783514	740308	TRUMATCH	Type:
Polished Brass (US3)	512418	740894	TRUMATCH	Job:
Oil Rubbed Bronze (US10B)	791699	740316	TRUMATCH	Order Code:
Antique Brass (US5)	754986	755009	TRUMATCH	Approvals:
PVD Brass	512434	740290		

Design House reserves the right to make changes in materials, specifications & models at any time. Design House also reserves the right to discontinue product without notice or obligation.