SPRINGDALE Passage Lever



Specifications

Latch Type 2-Way Latch & Universal Latch available

Door Prep Cross bore 2-1/8" dia (54mm). Edge bore 1" dia

(25mm)

Backset Adjustable to 2-3/8" or 2-3/4" **Door Thickness** 1-3/8" - 1-3/4" door standard

Cylinder -

Faceplate 1" x 2-1/4" radius corner. (Square and drive-in also

available on Universal)

Strike Standard radius corner . Other options available.


Latch Bolt Full 1/2" throw. Nickel plated.


Door Handing Non-handed. Reversible for Left or Right hand doors.

Keyway — Keyed Alike —



Dimensions





Warranty & Compliances

Warranty Limited Lifetime Mechanical / 5 year Finish

ANSI/BHMA Meets ANSI Grade 3 specification

ADA N/A UL N/A







Order Codes

Box Pack	2W	Universal	
Satin Nickel (US15)	700484	742841	TRUMMATCH
Polished Brass (US3)	700443	742817	TRUMMATCH
Oil Rubbed Bronze (US10B)	700526	742932	TRUMMATCH
Rustic Pewter	701375		TRU

View Pack

VIEW FACK			
Satin Nickel (US15)	742478		TRUM
Polished Brass (US3)	742445		TRU
Oil Rubbed Bronze (US10B)	742569	754846	TRU
Rustic Pewter	701334		TRUGAMA

Type: Job:

Order Code: Approvals:

Design House reserves the right to make changes in materials, specifications & models at any time. Design House also reserves the right to discontinue product without notice or obligation.