SPRINGDALE Entry Lever

KW1



Specifications

Latch Type	2-Way Latch & Universal Latch available					
Door Prep	Cross bore 2-1/8" dia (54mm). Edge bore 1" dia (25mm)					
Backset	Adjustable to 2-3/8" or 2-3/4"					
Door Thickness	1-3/8" - 1-3/4" door standard					
Cylinder	5-pin High Security - removable core					
Faceplate	1" x 2-1/4" radius corner. (Square and drive-in also available on Universal)					
Strike	Standard radius corner . Other options available.					
Latch Bolt	Full 1/2" throw. Nickel plated.					
Door Handing	Non-handed. Reversible for Left or Right hand doors.					


KA4 - 4 entries keyed alike




Dimensions

Keyway

Keyed Alike





Warranty & Compliances

Warranty	Limited Lifetime Mechanical / 5 year Finish Meets ANSI Grade 3 specification			heets	ANG	LIFETIME REAL		
ANSI/BHMA				GRA	DE 3			
ADA	N/A				,au			
UL	N/A							
Order Codes								
Box Pack		2W	Universal					
Satin Nickel (US15)		700500	742866	TRU				
Polished Brass (US3)		700468	742833	TRUMMATCH				
Oil Rubbed Bronze (U	S10B)	700542	742957	TRUMMATCH				
Rustic Pewter		701367		TRU				
View Pack					Type:	:		
Satin Nickel (US15)		742494		TRU	Job:			
Polished Brass (US3)		742460		TRU	Orde	r Code:		
Oil Rubbed Bronze (U	S10B)	742585	754820	TRU	Appro	ovals:		
Rustic Pewter		701326		TRUMATCH				

Design House reserves the right to make changes in materials, specifications & models at any time. Design House also reserves the right to discontinue product without notice or obligation.